SONY

like.no.other™

MDR-NC50

SPECIALTY	
Category	Noise cancelling
Subcategory	
General data	
Type	Closed, Dynamic
Driver unit	40mm
Sensitivty (NC power on/off)	102 / 100 dB/mW
Impedance (NC power on/off)	40 / 100 ohms
Magnet	Neodymium
Frequency response	14-22,000 Hz
Power handling capacity	100mW
Noise reduction effective range	40-1,500 Hz
Noise reduction rate	More than 10dB at around 300 Hz
Power source	DC 1.5V or 1 AAA battery
Power switch	Manual
Battery life	Approx. 30H with 1 AAA battery
Headband	Adjustable double band
Cord	OFC single sided detachable
Cord length	1.5m
Plug	L shaped gold plated stereo mini plug
Volume control	–
Noise canceling ON/OFF switch	ON/OFF switch on housing
Foldable	Swivel
Weight of headphones	Approx. 290 g (including AAA battery)
Noise Reduction %	80% (Eliminates 4/5 of noise)
Supplied accessories	
	Carrying Case
	Inflight Plug adapter
	Unimatch Plug adapter
	1.5m connecting cord
Package	
Style	Box
Dimensions (WxHxD in cm)	42.2x30.2x28.3
Package per Carton	4